



# MARKED UP VERSION OF SPECIFICATION

## Shift Mechanism For A Bicycle Gear Assembly

[Description]

### BACKGROUND OF THE INVENTION

5

The invention relates to a shift mechanism for a bicycle gear[s] assembly [in accordance with the precharacterizing clause of claim 1] and in particular a shift mechanism that includes an actuating lever and a  
10 release lever that operate independently from each other to shift between the gears.

EP 0 352 733 B1 [has] disclose[d]s a shift mechanism for a bicycle gear[s] assembly [in which the object is to  
15 create an improved shift mechanism, the mechanism being] that is a trigger shift mechanism, in which the tension cable can be wound up against the spring of the bicycle gear and released by a detent mechanism through the actuation of a single lever. This [object] is achieved  
20 [with] by an actuating lever [which is] rotatably mounted [in such a way that it can rotate] about a central axis to tension the tension cable[,]. [o]One detent device is traversed per shift step. [being traversed from gear ratio to gear ratio and this being capable of being  
25 relieved by means of a] A release lever is actuated to cause [in such a way that] the actuating lever [is] to be pulled back by the tension cable into the next detent stage for the next gear ratio. The release lever is an integral part of the actuating lever[,]. [t]The release  
30 lever being operated in a plane perpendicular to the plane of operation of the actuating lever. The pivot for the release lever is integrated into the actuating lever and, as the individual gear ratios are selected, corotates about the central axis of the actuating lever[,]

B

with the result that,] A drawback associated with this configuration is that in the extreme positions of the shift mechanism, between the hill-climbing gears and the speed gears, [the positions for] the actuating lever  
 5 [which are reached are] is located in an area which is ergonomically unfavorable [for the ergonomics of shifting].

[According to] French Patent FR 2 701 917 (93  
 10 02255)[,] discloses a [the] release lever and [the] an actuating lever that are arranged in two [mutually] parallel planes of action. [, it being possible for] This configuration allows an actuating part to be turned by the actuating lever about a common central axis, while  
 15 the release lever resets [said] the part, gear ratio by gear ratio by means of a toothed rocker bar.[, which] The manner in which the rocker bar engages [in] the tothing on the actuating part[, as with] is similar to a toothed rocker bar in a mechanical clock, which is  
 20 actuated by a balance.

#### Summary of the Invention

[The solution proposed by t]This invention combines  
 25 the [inventive] features of EP 352 733 with the [inventive] features of FR 2 701 917 inasmuch as a release lever [acts on] engages a first toothed segment and [a release lever acts on] a second toothed segment[.,]. [t]The two levers acting in planes that are  
 30 parallel to one another[.,]. [t]The two toothed segments [being] are connected by a detent element designed as a rocker and having detent noses that can [engage] alternately engage in one set of tothing of the toothed segments or the other. The detent element is controlled

B

by the release lever.[,] [t]The release lever [having arranged in it] has a cam contour connected to the detent element by means of an extension[,]. [t]The detent element [being able to] engages repeatedly and alternately [in] the toothing of the two toothed segments when the release lever is actuated in one direction. The detent element is spring-loaded toward the toothed segment on the actuating lever and [in this way adopts] thus the detent element is in its rest position when it is engaged [in engagement] with this toothed segment. [If] When the first toothed segment is [then] turned by the actuating lever, the detent element slides over the toothed segment, and the extension of the detent element is released from the cam contour of the release lever without performing an action.

A tension cable, which is wound up by the rotation of the toothed segment by means of the actuating lever, changes gear ratios in the bicycle gear and simultaneously tensions the cable against a spring in the bicycle gear. This tensioning can take place from the first to the last gear ratio. The release lever relaxes the cable and the toothed segments are moved back tooth by tooth, [and] gear ratio by gear ratio. During this process, the release lever's cam contour, which comprises a rising cam part and a falling cam part, first [of all] moves the detent element into a position of engagement and then out of a position of engagement with the toothed segment. If the release lever is released, the extension on the detent element moves backward over the cam contour and a second gear change is performed. [It appears appropriate to extend the] The cam contour may be extended [as regards its cam parts and] to provide a plurality of rising and falling cam parts. This means

that a plurality of gears can be shifted in a forward movement of the release lever, an equal number of gear change operations being added during the return of the release lever. Since the actuating lever is connected to the first toothed segment by a pawl, the actuating part is moved by the actuation of the release lever, this movement by the pawl being decoupled from the actuating lever.

It is therefore the object of the invention to create a shift mechanism for actuating a bicycle gear assembly which is designed as a trigger shift mechanism and can actuate a cable to shift one or more gear ratios not just in a direction of rotation corresponding to the winding up of the cable but can also shift via at least one but also via a plurality of gear ratios in a direction of rotation corresponding to the unwinding of the cable through the release of the cable.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The solution is described in the characterizing part of the main claim and in the subclaims. A shift mechanism having the features described in the statement of the object will be explained with reference to a number of drawings, in which:

Fig. 1 shows a shift mechanism for a bicycle, having a housing, an actuating lever and a release lever, and a detent element actuated by the release lever;

Fig. 2 shows the shift mechanism, having an actuating part and two toothed segments, into which the detent element actuated by the release lever engages;

Fig. 3 shows the release lever with a cam contour for the actuation of the detent element;

5 Fig. 4 shows the cam contour in the release lever with a plurality of rising and falling cam parts; and

Fig. 5 shows the actuating lever with a pawl that can be operated on the housing side and is intended to  
10 interact with tothing on a second detent disk.

#### DETAILED DESCRIPTION OF THE INVENTION

09700788-110000  
The invention describes a bicycle-gear shift  
15 mechanism that can be arranged on bicycle handlebars and controls [this] a bicycle gear assembly. According to Fig. 1, the shift mechanism [comprises] includes a housing 2 with an actuating part 3 that can be moved by an actuating lever 1 and by a release lever 10. The  
20 actuating part 3 has a winding groove 4 for a tension cable 5, which is connected to the bicycle gear assembly and is kept under tension by a spring located there. The actuating part 3 has a first detent disk 16 with a first toothed segment 8 and a second detent disk 17 with a  
25 second toothed segment 9[.]. [t]The actuating part 3 [being arranged in such a way] having a configuration such that it can rotate about a central axis 11 with the first detent disk 16 and the second detent disk 17. The actuating part 3 can be turned by the actuating lever 1  
30 by means of a pawl 6, [this pawl 6] which engag[ing]es in tothing 7 connected rotationally to the actuating part 3. When the actuating lever 1 is moved, this movement is transmitted to the actuating part 3 by the pawl 6, [in this way] resulting in [winding] the cable 5 being wound

onto the winding groove 4, and thereby tensioning the spring and changing gear ratios in the bicycle gear assembly.

5 Fig. 2 shows a play-free trigger device in the form of a detent element 12 [with] having a first detent nose 13 and a second detent nose 14[,]. The detent element 12 [which] is arranged pivotably on a pivot 15 fixed in relation to the housing[, it being ensured that the intersection of] [t]The first detent nose 13 engages 10 [with] the first toothed segment 8 and [that of] the second detent nose 14 engages [with] the second toothed segment 9 [can take place] alternatively. The detent element 12 is supported against the housing by a spring 15 23 and interacts by means of the second detent nose 14 with the second toothed segment 9 of the second detent disk 17 in the state of rest, thereby ensuring that, once a gear ratio has been selected in the bicycle gear assembly, it is retained. The detent element 12 has an 20 extension 20 that interacts with a cam contour 19 in the release lever 10. The extension 20 is held in continuous contact with an edge 18 by the spring 23 and, when the release lever 10 is actuated, the extension 20 slides on [this] the cam contour 19, resulting in the detent 25 element 12 [having imposed on it] performing a rocking motion [that ensures that] causing the second detent nose 14 and the first detent nose 13 to alternately [enter into engagement with] engage the second toothed segment 9 and the first toothed segment 8, respectively.

30

[From] Referring to Figs. 3 and 4, [it can be seen that] the cam contour 19 has at least one rising cam part 21 and one falling cam part 22, along which the extension 20 must slide. To [effect] release [of] the cable 5 [for

the purpose of shifting the] to shift between gear ratios  
 [in the bicycle gear], the release lever 10 is actuated  
to disengage the retaining connection between the second  
detent nose 14 and the second toothed segment 9,  
 5 resulting in the actuating part being turned by the cable  
in the winding groove 4 which is being pulled back gear  
ratio by gear ratio by the spring situated on the bicycle  
gear assembly. [detent the spring situated in this  
 bicycle gear pulls the cable 5 back gear ratio by gear  
 10 ratio, the actuating part 3 being turned by means of the  
 winding groove 4 when the release lever 10 disengages the  
 retaining connection between the second detent nose 14  
 and the second toothed segment 9.] In this case, the  
 extension 20 of the detent element 12 [has] runs up onto  
 15 the rising cam part 21 of the cam contour 19, the release  
 lever 10 [having] has turned through a partial angle W  
 and the first detent nose 13 [having] has entered into  
 engagement with the first toothed segment 8. [In this  
 case - as is customary with trigger shift mechanisms -]  
 20 When the cable 5 has been released from the winding  
 groove 4 by about half a gear ratio; the second half of  
 the gear ratio is traversed by virtue of the fact that,  
 in accordance with Fig. 3, the extension moves back on  
 the falling cam part 22 into its original position,  
 25 provided that the release lever 10 is turned by a further  
 partial angle W.

In [the manner of] trigger shift mechanisms, all the  
 levers return to their starting position through spring  
 30 force once shifting of the gear ratios in the bicycle  
 gear has been completed, which means that the release  
 lever 10 shown in Fig. 3 can shift a maximum of two gear  
 ratios with its cam contour 19 in the direction of  
 rotation corresponding to the unwinding of the cable. If

only one gear ratio is to be shifted, it is sufficient to turn the release lever 10 merely through a partial angle W until the extension 20 has reached the end of the rising cam part. If the release lever 10 is then released, it returns to its starting position, and the extension 20 returns to its original position. Since, in accordance with Fig. 4, the cam contour 19 has four partial angles W, i.e. two rising cam parts 21 and two falling cam parts 22, it is possible to shift a maximum of 4 gears if the release lever 10 is turned until the extension 20 has traversed all cam parts 21 and 22 in both directions. To make it easier to shift the gear ratios in the bicycle gear assembly, a detent can be built into the release lever 10, making it easier for the rider to find the individual end points for the travel of the release lever 10 for the planned gear ratios.

Fig. 5 shows an actuating lever 1, which, in the position indicated, occupies a rest position N as long as the first and last gear ratios of the bicycle gear are not selected. Arranged on the second detent disk 17 or actuating part 3 is a stop extension 27, which interacts with a first stop 25 and a second stop 26 on the actuating lever 1 when the first gear ratio or last gear ratio is selected in the bicycle gear. Assuming that the first gear ratio is selected when the stop extension 27 has been turned into the outermost position counter to the direction of rotation, the first stop 26 is designed [in] such [a way] that the actuating lever 1 can no longer return to its rest position N and remains in a rest position I of the first gear ratio. Such a measure indicates to the rider by feel that all the gear ratios have been traversed and that the first gear ratio has been reached. It should likewise be communicated to the



rider by feel that shifting further would be pointless through a rest position II of the last gear ratio. This is achieved by virtue of the fact that the stop extension 27 runs clockwise against the first stop 25, thereby preventing the actuating lever 1 from returning to the rest position N.

00021 880060

The advantage of [a shift mechanism designed in accordance with] the present invention is that it is possible [to a large extent] to shift through the gear ratios of the bicycle gears both with the actuating lever 1 and with the release lever 10[,]. [t]The detent element 12 of both levers 1 and 10 being decoupled [in] such [a way] that the movements of one lever 1 or 10 are not transmitted to the other lever 1 or 10 [but] while the trigger principle, namely the ability to select individual gear ratios, is maintained and both levers 1, 10[, namely the actuating lever 1 and the release lever 10,] always return to their respective initial positions.

The [proposed design of a shift mechanism] present invention also allows the first and the last gear ratios to occupy rest positions I and II that are different from the normal rest position N in order to indicate the end points of the shift steps to the rider by feel without the need to make visual contact with a gear display.

B